SG2.0/3.0RS-S

Single-MPPT String Inverter for 600 Vdc System



HIGH YIELD

- Compatible with high power PV modules and bifacial modules
- Lower startup & wider MPPT voltage range
- Built-in smart PID Zero function

SAFE AND RELIABLE

- Integrated arc fault circuit interrupter
- Built-in Type II DC&AC SPD
- Corrosion protection rating at C5

USER FRIENDLY SETUP

- Plug and play installation
- One-click access to iSolarCloud monitoring platform
- Light and compact (A4 Size) with optimized heat dissipation design

SMART MANAGEMENT

- Real time data (10 seconds refresh sample)
- 24/7 live online monitoring and with integrated display
- Online IV curve scan and diagnosis

CIRCUIT DIAGRAM



EFFICIENCY CURVE (SG3.0RS-S)



© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1

Type designation	SG2.0RS-S	SG3.0RS-S
Input (DC)		
Recommended max. PV input power	3 kWp	4.5 kWp
Max. PV input voltage	600 V	
Min. operating PV voltage / Start-up input voltage	40 V / 50 V	
Rated PV input voltage	360 V	
MPP voltage range	40 V – 560 V	
No. of independent MPP inputs	1	
Default No. of PV strings per MPPT	1	
Max. PV input current	16 A	
Max. DC short-circuit current	20 A	
Output (AC)		
Rated AC output power	2000 W	3000 W
Max. AC Output power	2000 VA	3000 VA
Rated AC output current (at 230 V)	8.7 A	13.1 A
Max. AC output current	9.1 A	13.7 A
Rated AC voltage	220 V / 230 V / 240 V	
AC voltage range	154 V - 276 V	
Rated grid frequency / Grid frequency range	50 Hz / 45 - 55 Hz 60 Hz / 55 - 65 Hz	
Harmonic (THD)	< 3 % (at rated power)	
Power factor at rated power / Adjustable power factor	> 0.99 / 0.8 leading - 0.8 lagging	
Feed-in phases / Connection phases	1 / 1	
Efficiency		
Max. efficiency / European efficiency	97.8 % / 96.9 %	97.8 % / 97.3 %
Protection		
Grid monitoring	Yes	
DC reverse polarity protection	Yes	
AC short-circuit protection	Yes	
Leakage current protection	Yes	
Surge Protection	DC type II / AC type II	
DC switch	Yes	
PV string current monitoring	Yes	
Arc fault circuit interrupter (AFCI)	Yes	
PID Zero function	Yes	
General Data		
Dimensions (W * H * D)	320 mm * 225 mm * 120 mm	
Weight	6 kg	
Mounting method	Wall-mounting bracket	
Topology	Transformerless	
Degree of protection	IP65	
Operating ambient temperature range	-25 ℃ to 60 ℃	
Allowable relative humidity range (non-condensing)	0 % - 100 %	
Cooling method	Natural cooling	
Max. operating altitude	4000 m	
Display	LED digital display & LED indicator	
Communication	Ethernet / WLAN / RS485 / DI (Ripple control & DRM)	
DC connection type	MC4 (Max. 6 mm^2)	
AC connection type	Plug and play connector (Max. 6 mm^2)	
Grid compliance	IEC / EN62109-1/2, IEC / EN62116, IEC / EN61727, IEC / EN61000-6-2/3, EN50549-1, AS4777.2, UNE 217002:2020, NTS V2 TypeA, CEI 0-21:2020, VDE0126-1-1/ A1 (VFR-2019), UTE C15-712, C10/11, G98/G99	
Grid Support	Active & reactive power control and power ramp rate control	

© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1