SH10/12T

Hybrid Three Phase Inverter



FULL BACKUP

- Built-in 63 A bypass for whole home backup
- 10 ms seamless switch
- Peak output up to 16800 VA (10 s) in backup mode (SH12T)

FLEXIBLE APPLICATION

- Support 100% unbalance output in backup and on grid mode
- Max. 16 A DC input current per string
- 50 A fast charge / discharge current

FRIENDLY INSTALLATION

- Plug & Play installation
- Quiet operation for indoor or outdoor installation

SAFE AND DURABLE

- Support precise AFCI
- IP65/C5

© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1

Type designation	SH10T	SH8T	SH12T
Input (DC)			
Recommended max. PV input power	20000 Wp		24000 Wp
Max. PV input voltage *		1000 V	
Min. PV input voltage / Startup input voltage		150 V / 180 V	
Rated PV input voltage		600 V	
MPPT operating voltage range **		150 V - 950 V	
No. of independent MPP trackers		2	
No. of PV strings per MPPT		2 / 1	
Max. PV input current		48 A (32 A / 16 A)	
Max. DC short-circuit current		60 A (40 A / 20 A	
Max. current for input connector		30A	
Battery data			
Battery type		Li-ion battery	
Battery voltage		100 V - 700 V	
Max. charge / discharge current ***		50 A / 50 A	
Max. charge / discharge power	15000W/10000W		15000W/12000W
Input and Output (AC)			
Max. AC power from grid ****		43000 VA	
Rated AC output power	10000 W		12000 W
Max. AC output apparent power	10000 VA		12000 VA
Max. AC output current	15.2 A		18.2 A
Rated AC voltage		3 / N / PE , 220 V / 380 V ; 230 V / 400 V ; 240 V / 415 V	
AC voltage range		270 V - 480 V	
Rated grid frequency		50 Hz / 60 Hz	
Grid frequency range		45 Hz - 55 Hz / 55 Hz - 65 Hz	
Harmonic (THD)		< 3 % (of rated power)	
Power factor at rated power / Adjustable power factor		> 0.99 / 0.8 leading to 0.8 lagging	
Feed-in phases/connection phases		3 / 3-N-PE	
Backup data (on grid mode)			
Max. output power for backup load ****		43000 W	
Max. output current for backup load		3 * 63 A	
Backup data(off-grid mode)			
Rated voltage		3 / N / PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V (± 2 %)	
Rated frequency		50Hz / 60Hz (± 0.2 %)	
THDV(@Linear load)		2 %	
Backup switch time		< 10 ms	
Rated output power	10000W / 10000VA		12000W / 12000VA
Peak output power *****	15000 W / 15000 VA,10 s		16800 W / 16800 VA,10 s
Efficiency			
Max. efficiency / European efficiency	98.0 % / 97.5 %		98.0 % / 97.5 %
Protection & Function			
Grid monitoring		Yes	
DC reverse polarity protection		Yes	
AC short-circuit protection		Yes	
Leakage current protection		Yes	
DC switch (solar)		Yes	
Surge protection		DC Type II / AC Type II	
PID zero		Yes	
Battery input reverse polarity protection		Yes	
General data			
Topology (solar / battery)		Transformerless / Transformerless	
Degree of protection		IP65	
Dimensions (W * H * D)		620 mm * 480 mm * 195 mm	
Weight		32 kg	
Mounting method		Wall-mounting bracket	
Operating ambient temperature range		-25 ℃ - 60 ℃	
Allowable relative humidity range(Non-condensing)		0 % - 100 %	
Cooling method		Natural convection	
Max. operating altitude		2000	
Noise(Typical)		35 dB (A)	
Display		LED	
Communication		RS485, WLAN, Ethernet, CAN	
DI / DO		DI * 4 / DO * 2 / DRM0	
DC connection type		MC4 compatible connector (PV, Max.6 mm²) /Plug and play connector (battery, Max.10 mm²)	
AC connection type		Plug and play connector (Max.16 mm²)	
Compliance		IEC / EN 62109, IEC 61000-6, EN 62477-1, IEC 61727, IEC 62116, IEC 62920, EN 55011, CISPR 11, VDE-AR-N-4105, EN 50549-1, AS/NZS 4777.2:2020, TOR Type A, R25, NC RFG, PSE 2018, NTS V2.1 Type A, UNE217001, UNE 217002, RD, CEI 0-21	

* Input voltage exceeding the MPPT operating voltage range triggers inverter protection
** Please refer to the user manual for the full load MPPT voltage range
*** Depending on the connected battery
**** Please refer to the user manual and modify the settings based on actual load power
***** Can be reached only if PV and battery power is sufficient

© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1