SH15/20/25T

Hybrid Three Phase Inverter



FULL BACKUP

- Built-in 63 A bypass for whole home backup
- 10 ms seamless switch
- Peak output up to 36500 VA (10 s) in backup mode (SH25T)

FLEXIBLE APPLICATION

- Support 100 % unbalance output in backup and on grid mode
- Max. 16 A DC input current per string
- 50 A fast charge / discharge current

FRIENDLY INSTALLATION

- Plug & Play installation
- Quiet operation for indoor or outdoor installation

SAFE AND DURABLE

- Support precise AFCI
- IP65/C5

© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1

Type designation	SH15T	SH20T	SH25T
Input (DC)			
Recommended max. PV input power	30000 Wp	40000 Wp	50000 Wp
Max. PV input voltage *	1000 V		
Min. PV input voltage / Startup input voltage	150 V / 180 V		
Rated PV input voltage	600 V		
MPPT operating voltage range **	150 V - 950 V		
No. of independent MPP trackers	3		
No. of PV strings per MPPT	2 / 2 / 1		
Max. PV input current	80 A (32 A / 32 A / 16 A)		
Max. DC short-circuit current	100 A (40 A / 40 A / 20 A)		
Max. current for input connector	30 A		
Battery data			
Battery type	Li-ion battery		
Battery voltage range	100 V - 700 V		
Max. charge / discharge current ***	50 A / 50 A		
Max. charge / discharge power	30000 W / 15000 W	30000 W / 20000 W	30000 W / 25000 W
Input and Output (AC)			
Max. AC power from grid ****	43000 VA		
Rated AC output power	15000 W	20000 W	25000 W
Max. AC output apparent power	15000 VA	20000 VA	25000 VA
Max. AC output current	22.8 A	30.4 A	37.9 A
Rated AC voltage	3 / N / PE, 220 V / 380 V ; 230 V / 400 V; 240 V / 415 V		
AC voltage range	270 V - 480 V		
Rated grid frequency	50 Hz / 60 Hz		
Grid frequency range	45 Hz - 55 Hz / 55 Hz - 65 Hz		
Harmonic (THD)	< 3 % (of rated power)		
Power factor at rated power / Adjustable power factor	> 0.99 / 0.8 leading to 0.8 lagging		
Feed-in phases / connection phases	3 / 3-N-PE		
Backup data(on grid mode)			
Max. output power for backup load ****	43000 W		
Max. output current for backup load	3 * 63 A		
Backup data(off-grid mode)			
Rated voltage	3 / N / PE, 220 / 380 V; 230 / 400 V; 240 / 415 V (± 2 %)		
Rated frequency	50 Hz / 60 Hz (± 0.2 %)		
THDV (@Linear load)	2 %		
Backup switch time	< 10 ms		
Rated output power	15000 W / 15000 VA	20000 W / 20000 VA	25000 W / 25000 VA
Peak output power *****	25500 W / 25500 VA ,10 s	32000 W / 32000 VA ,10 s	36500 W / 36500 VA ,10 s
Efficiency			
Max. efficiency / European efficiency	98.1 % / 97.6 %		98.2 % / 97.8 %
Protection & Function			
Grid monitoring	Yes		
DC reverse polarity protection	Yes		
AC short-circuit protection	Yes		
Leakage current protection	Yes		
DC switch (solar)	Yes		
Surge protection	DC Type II / AC Type II		
PID zero	Yes		
Battery input reverse polarity protection	Yes		
General data			
Topology (solar / battery)	Transformerless / Transformerless		
Degree of protection	IP65		
Dimensions (W * H * D)	620 mm * 480 mm * 245 mm		
Weight	38 kg		40 kg
Mounting method	Wall-mounting bracket		
Operating ambient temperature range	-25 ℃ - 60 ℃		
Allowable relative humidity range(Non-condensing)	0 % - 100 %		
Cooling method	Natural convection		Fan cooling
Max. operating altitude	2000 m		
Noise(Typical)	35 dB (A)		50 dB (A)
Display	LED		
Communication	RS485, WLAN, Ethernet, CAN		
DI / DO	DI * 4 / DO * 2 / DRM0		
DC connection type	MC4 compatible connector (PV,Max.6 mm²) /Plug and play connector (battery, Max.10 mm²)		
AC connection type	Plug and play connector (Max.16 mm²)		
Compliance	IEC / EN 62109, IEC 61000-6, EN 62477-1, IEC 61727, IEC 62116, IEC 62920, EN 55011, CISPR 11, VDE-AR-N-4105, EN 50549-1, NRS 097, AS/NZS 4777.2:2020, TOR Type A, R25, CEI 0-21		

* Input voltage exceeding the MPPT operating voltage range triggers inverter protection
** Please refer to the user manual for the full load MPPT voltage range
*** Depending on the connected battery
**** Please refer to the user manual and modify the settings based on actual load power
***** Can be reached only if PV and battery power is sufficient

© 2026 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1